

SUPER TWIST-LOK®

Heavy Duty

2'-4' (0.6 m - 1.2 m) extension pole - Model #5204

4'-8' (1.2 m - 2.4 m) extension pole - Model #5208

6'-12' (1.8 m - 3.6 m) extension pole - Model #5212

8'-15' (2.4 m - 4.5 m) extension pole - Model #5216

SPECIFICATIONS: 1-1/4" (3.2 cm) diameter round fiberglass handle and 1" (2.5 cm) diameter round fiberglass slider tube

PACK QUANTITY: 6



Smooth Fiberglass Construction

- Smooth round fiberglass handle and slider with large rubber hand grip.
- Die cast metal universal threaded end fits most standard threaded tools.
- Lok-Thread™ on threaded end prevents roller frames and tools from loosening during use.

Internal Locking Device

- Bi-directional locking mechanism locks in either direction at any extended length.
- “Click” sound lets you know the slider is locked in place and will not slip.



COMPOSITE TECHNOLOGY

The Pultrusion process is utilized to manufacture tubing for extension poles. Space-age composite resins saturate the reinforcement fibers then heat and pressure are applied to activate the catalyst in the resin mix and lock the fibers together. The resulting composite tube has a fiber orientation designed to maximize tensile and flexural properties. The process produces excellent rigidity with superior transverse and burst strengths.



Use SUPER TWIST-LOK to get all these jobs done.



1-800-821-3508
www.mrlongarm.com

MR. LONG ARM
Finish. Up.