

- 2'-4' (0.6 m – 1.2 m) extension pole - Model #3204
- 3'-6' (0.9 m – 1.8 m) extension pole - Model #3206
- 4'-8' (1.2 m – 2.4 m) extension pole - Model #3208
- 6'-12' (1.8 m – 3.6 m) extension pole - Model #3212
- 8'-15' (2.4 m – 4.6 m) extension pole - Model #3216

SPECIFICATIONS:

1-1/16" (2.7 cm) diameter fluted fiberglass handle and
7/8" (2.2 cm) diameter round aluminum slider tube

PACK QUANTITY: 6

Aluminum - Fluted Fiberglass

- The aluminum slider and fiberglass handle combination ensures that extension poles are better balanced and more rigid when telescoped.
- Fluted round fiberglass handle provides a better grip.
- Aluminum slider is anodized which prevents rust and provides a smoother extension.
- Nylon universal threaded end fits most standard threaded tools.



External Locking Device

- Compression mechanism locks at any extended length.
- Coarse threads provide quick lock and unlock and prevent over-tightening.
- End cap with hole for peghook or easy storage.



COMPOSITE TECHNOLOGY

The Pultrusion process is utilized to manufacture tubing for extension poles. Space-age composite resins saturate the reinforcement fibers then heat and pressure are applied to activate the catalyst in the resin mix and lock the fibers together. The resulting composite tube has a fiber orientation designed to maximize tensile and flexural properties. The process produces excellent rigidity with superior transverse and burst strengths.



Use PRO-POLE to get all these jobs done.



1-800-821-3508
www.mrlongarm.com

MR. LONGARM®
Finish. Up.